

Product consolidation OMNIMATE® Signal Connector pitch 5.0x BLZ 5.0x / BL 5.0x / BLZF 5.0x / SLZF 5.0x / SL 5.0x

Dear Madam or Sir,

we hereby inform you that the below listed articles has been subjected to be discontinued and will no longer be available after a transitional period. Please pass this product information only to your employees and possibly to your customers

1. General Overview

Type of notification: ☐ PCN ☒ PDN ☐ Short-term action (<6 months)

Short-term action due to:

- | | |
|--|---|
| <input type="checkbox"/> Software / Firmware Bugfix | <input type="checkbox"/> Short term delivery stop by supplier |
| <input type="checkbox"/> Short term recall by supplier | <input type="checkbox"/> Force majeure |
| <input type="checkbox"/> Product improvement with customer benefit | <input type="checkbox"/> other |
-

2. General Information

Technological change, ecological action and competitive supply security require temporary product adjustments or even consolidations. Our phase-out strategy supports you with possible equipment adjustments.

Target of this strategy is:

- To drive technological change with our customers.
Customer benefits: General product improvements for successor articles
 - To establish ecological action in our processes
Customer benefits: Lower CO2 emissions by avoiding inefficiencies
 - Reduce complexity through product and function consolidation
Customer benefits: Improved delivery and supply security
 - To support possible appliance adaptations in parallel
Customer benefits: Extended supply for long-term storage
-





















3. Availability







- | | |
|------------------------------|-------------------|
| • Start of Production (SoP): | - |
| • End of Sales (EoS): | 31.07.2023 |
| • End of Delivery (EoD): | 31.03.2024 |
| • End of Life/Service (EoL): | 31.12.2024 |









Final orders could be placed by 31.07.2023, with final deliveries planned by 31.03.2024.

You are welcome to discuss further options such as a "last call" or a "life-time-buy" over a period of up to 10 years directly with us.

4. Product comparison

| BLZ 5.0x | | BLZP 5.0x | |
|---|---|--|---|
|  |  |  |  |
|  |  |  |  |
| Technical data | | Technical data | |
| <ul style="list-style-type: none"> - Clamping range: 0.5 – 2.5 mm² - I_{max}: 18,5 A (IEC); 15 A (UL) - | | <ul style="list-style-type: none"> - Clamping range: 0.2 – 4 mm² - I_{max}: 23 A (IEC); 20 A (UL) - Plus– minus screw, wireguard | |
| BL 5.0x | | BLZP 5.0x | |
|  | |  | |
|  | |  | |
| Technical data | | Technical data | |
| <ul style="list-style-type: none"> - Clamping range: 0.5 – 1.5 mm² - I_{max}: 14 A (IEC); 10 A (UL) | | <ul style="list-style-type: none"> - Clamping range: 0.2 – 4 mm² - I_{max}: 23 A (IEC); 20 A (UL) - Plus– minus screw, wireguard | |
| BLZF 5.0x | | BLF 5.0x | |
|  |  |  |  |
|  |  |  |  |
| Technical data | | Technical data | |
| <ul style="list-style-type: none"> - Clamping range: 0.5 – 2.5 mm² - I_{max}: 17 A (IEC); 10 A (UL) | | <ul style="list-style-type: none"> - Clamping range: 0.2 – 2.5 mm² - I_{max}: 24 A (IEC); 18.5 A (UL) - Reduce installation time | |

| SLZF 5.0x | | SLF 5.0x | |
|--|---|--|--|
|  |  |  | |
|  |  |  | |
| Technical data | | Technical data | |
| <ul style="list-style-type: none"> - Clamping range: 0.5 – 2.5 mm² - I_{max}: 17 A (IEC); 10 A (UL) | | <ul style="list-style-type: none"> - Clamping range: 0.2 – 2.5 mm² - I_{max}: 24 A (IEC); 18.5 A (UL) | |

| SL 5.08 | | SL 5.08HC | |
|--|--|--|--|
|  |  |  |  |
|  |  |  |  |
| Technical data | | Technical data | |
| <ul style="list-style-type: none"> - I_{max}: 18 A (IEC); 15 A (UL) | | <ul style="list-style-type: none"> - I_{max}: 24 A (IEC); 18 A (UL) | |

5. Affected parts

A list of the affected articles and their successors can be found attached. If a part you have purchased so far does not have a direct successor, please contact your sales representative.

We are very sorry for all the inconveniences caused and doing everything to adjust this product change as smooth as possible without big influence on delivery times and general functions.

For further questions please contact your sales office directly. All contacts for sales representatives are available here:

<http://www.weidmueller.com/contact>

Weidmüller will see this notification as accepted unless a separate procedure is requested in writing within 30 days of the issue date

Best regards

Product Management

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16, 32758 Detmold, Germany



Weidmueller – Your partner in Industrial Connectivity
We look forward to sharing ideas with you – **Let's connect.**