



End plate, Width: 1.6 mm, Colour: Beige

Business data

Article number	3795.2
Article name	ZAP SR 3A/35 BG
GTIN (EAN)	4044211061272
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	1.9 g
Weight per piece (including packaging)	1.95 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	3795.2
Product description	End plate

Technical data

Dimensions

Length	54.2 mm
Width	1.6 mm
Height	28.7 mm

Further technical data

Material	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C
Designed as end plate	✓
Snap-on available	✓

Materials

Material	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-01-07, 2022-06-10
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

Accessories

##INVERSE##CONTA-CONNECT




Ex protective-earth terminal ATEX-certified Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1712.2</u>	ZSLN 2,5/3A Ex GNYE	4044211059668	100 ST




Protective earth terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3602.2</u>	ZSLN 2,5/3A GNYE	4044211152055	100 ST



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1703.2</u>	ZSRK 2,5/3A Ex BG	4044211059620	100



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3600.2</u>	ZSRK 2,5/3A BG	4044211152031	100