





Insulated cross-connector, No. of poles: 6, Mounting type: Plug in, Width: 46.7 mm, Rated cross-section: 6 mm², Colour: Yellow

RAL: 1026

Business data

Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	7 g
Weight per piece (including packaging)	7.1 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	17225.8
Product description	Insulated cross-connector



17225.8 SQI 6/6 YE

Technical data		
Dimensions		
Length	4 mm	
Width	46.7 mm	
Height	23 mm	
Pitch size	8 mm	
Ratings		
Voltage with partition, max.	1000 V	
Voltage without partition, max.	1000 V	
Rated current	41 A	
Current load, max.	41 A	
Rated cross-section	6 mm²	
Contamination degree	2	
Connection data		
No. of poles	6	
Materials		
Material	Copper alloy	
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-2	
Working temperature, min.	-40 °C	
Working temperature, max.	105 °C	
Further technical data		
Mounting type	Plug in	
Insulation available	✓	
Touch protection is available	✓	
Number of bridged terminals	6	
Print		
Colour	Yellow	



17225.8 SQI 6/6 YE

Technical data

Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2021-07-08	
REACH Candidate Substance Note	No	
RoHS Conform	yes	



SQI 6/6 YE



Accessories

Insulation cap for cross-connector



Insulating cap, Colour: Yellow

General order data

Product number: Article name GTIN (EAN) Packaging unit

17200.8 SQIK 2,5-10 YE 4044211148539 20