


17406.8
FIQI 2,5-4/6 YE



Insulated cross-connector, No. of poles: 6, Mounting type: Plug in, Width: 30 mm, Colour: Yellow

RAL: 1026

Business data

Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	3.5 g
Weight per piece (including packaging)	3.57 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	Insulated cross-connector

17406.8

FIQI 2,5-4/6 YE

Technical data

Dimensions

Length	3.4 mm
Width	30 mm
Pitch size	5.1 mm

Ratings

Max. voltage	800 V
Rated current	24 A
Current load, max.	32 A
Rated cross-section	2.5 mm ²
Contamination degree	2

Connection data

No. of poles	6
--------------	---

Materials

Material	Bronze
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	6

Print

Colour	Yellow
--------	--------

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2021-07-08
REACH Candidate Substance Note	No
RoHS Conform	yes

17406.8

FIQI 2,5-4/6 YE

Accessories
