

Data sheet

3789.8 ZQI 10/2 YE



Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 17.4 mm, Rated cross-section: 10 mm², Colour: Yellow

RAL: 1026

Business data

Article number	3789.8
Article name	ZQI 10/2 YE
GTIN (EAN)	4044211061173
Colour	Yellow
Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	7.4 g
Weight per piece (including packaging)	7.52 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Product description	Insulated cross-connector

Technical data

Dimensions

Length	7.6 mm
Width	17.4 mm
Pitch size	10 mm

Ratings

Voltage with partition, max.	1000 V
Voltage without partition, max.	1000 V
Rated current	57 A
Rated cross-section	10 mm ²
Contamination degree	3

Connection data

No. of poles	2
--------------	---

Materials

Material	Bronze
Surface	Tin-lead
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	2

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-06-10
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

Accessories

##INVERSE##CONTA-CONNECT



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 10.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3597.2</u>	ZRK 10/2A BG	4044211151997	50



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 10.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1720.2</u>	ZRK 10/2A Ex BG	4044211059569	50