

Harimatec – Label Change Notification for Solder Products

Date Prepared: 15/09/2023

Summary of Label Changes (Solder Wire, Solder Paste, Liquid Flux, Solder Wire)

- 1. Label Change Date: From 1st December 2023
- 2. Details of Change:

	Loctite Lo	ogo repl	laced wit	h Mu	lticore	Logo
--	------------	----------	-----------	------	---------	------

- ☐ Henkel Logo replaced with Harima and Multicore logo.
- ☐ Henkel address replaced with Harimatec Malaysia address
- ☐ Henkel emergency contact no (CHEMTREC) removed.
- ☐ The Loctite brand name will be replaced with Multicore brand name.
- "All marks are trademarks and/or registered trademarks of Henkel and its affiliates in the US and elsewhere" this statement will be removed.
- □ Pb-Free and RoHS symbols will be added for lead free solder paste and solder wire products (that comply to RoHS).
- ☐ "Known As" will be removed.



General Label Changes for All Products

Loctite Logo replaced with Multicore Logo



Harimatec Malaysia Sdn Bhd Lot 62049 Jalan Portland,Tasek Industrial Estate,31400 Jpoh, Perak Darul Ridzuan,Malaysia. Tel:60-5-5432000 Fax:60-5-6471868 Made in Malaysia

IDH: 322235



ALLOY:HMP

DIAMETER: 0.56MM TYPE: ERSIN 362 CORE: 5 CORE CONTENTS: 20 X 0.25KG REELS

NET WEIGHT: 5KG DOM: 17/May/2022

Bahan Pemetrian Mengandungi Plumbum. Soldering Material Containing Lead.

KNOWN AS: HMP 362 5C 0.56MM 0.25KG RLS

Refer SDS before use Rujuk SDS sebelum guna





"Known As" to be removed

Lead CAS:(7439-92-1) 60 - 100 %;Tin CAS:(7440-31-5) 1 - 10 %;Silver CAS:(7440-22-4) 1 - 10 %



(EN) Danger: May damage fertility or the unborn child. May cause harm to breast-fed children. Causes damage to organs (Blood, Kidney, Central Nervous system) through prolonged or repeated exposure (inhalation-dust, oral)

Prevention: Obtain special instructions before use. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact during pregnancy and while nursing. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF exposed or concerned: Get medical advice/attention.

(MS) Bahaya: Boleh merosakkan kesuburan atau janin. Boleh memudaratkan kanak-kanak yang menyusu badan Menyebabkan kerosakan organ(darah, ginjal, sistem saraf tunjang) dengan pendedahan berpanjangan atau berulang kali(penyedutan-habuk, oral).

Pencegahan: Dapatkan arahan khas sebelum menggunakannya. Jangan hirup habuk/wasap/gas/kabus/wap/semburan. Elakkan sentuhan semasa hamil/menyusu bayi. Basuh tangan bersih-bersih selepas mengendalikan bahan. Jangan makan, minum atau merokok apabila menggunakan produk ini. Pakai sarung tangan pelindung/pakaian pelindung/perlindungan mata/perlindungan muka.

Respons: JIKA mengalami pendedahan atau khuatir. Dapatkan nasihat/rawatan perubatan.

Henkel logo replaced with Multicore logo and Harima logo



General Label Changes for All Products

Henkel name changed to Harimatec Malaysia Sdn Bhd



Henkel's emergency call center number and "All marks are trademarks and/or registered trademarks of Henkel and its affiliates in the US and elsewhere" removed



Changes to Solder Paste Labels

Henkel Version



Henkel (M) Sdn Bhd Lot 62049 Jalan Portland, Tasek Industrial Estate, 31400 Ipoh Perak Darul Ridzuan, Malaysia. Tel:60-5-5476811 Fax:60-5-5471888

www.henkel.com/electronics Made in Malaysia

Henke



NET WT: 0.500KG DOM: 21/Sep/2022 USE BY:23/Mar/2023

FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call CHEMTREC: +1 703-741-5970

STORAGE COND: 0-10C

KNOWN AS: 96SC LF310 AGS88 500G/J OTO

Refer SDS before use Rujuk SDS sebelum guna.

All marks are trademarks and/or registered trademarks of Henkel and its affiliates in the US and elsewhere.

(EN) Warning: May cause an allergic skin reaction.

Prevention: Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF ON SKIN: Wash with pienty of water, if skin imitation or rash occurs; Get medical advice/attention. Take off contaminated clothing and wash it before

MS) Amaran: Boleh menyebabkan tindak balas alahan kulit.

Pencegahan: Elakkan daripada menghirup habuk/wasapigas/kabus/wapisemburan. Pakalan kerja yang tercemar tidak harus dibiankan keluar dari tempat kerja. Pakai sarung tangan pelindungipakaian pelindungiperindungan mata perindungan muka. Respons: JIKA TERKENA KULIT: Basuh dengan air yang banyak. Jika terjadi kerengsaan atau ruam kulit. Dapatkan nasihatirawatan perubatan. Tanggalkan

pakalan yang tercemar dan basuh sebelum digunakan semula.



Harima Version

MULTICORE

LF 310 96SCAGS88 BO

IDH: 537342

NET WT: 0.500KG DOM: 21/Sep/2022

USE BY:23/Mar/2023 STORAGE COND: 0-10C

Refer SDS before use. Rujuk SDS sebelum guna.

Harimatec Malaysia Sdn Bhd Lot 62049 Jalan Portland Tasek Industrial Estate 31400 Ipoh. Perak Darul Ridzuan Malaysia. Tel:60-5-5432000 Fax:60-5-5471868

O52J999061

PART NO: 5998510000

LOT NO:



Tin CAS:(7440-31-5) 60 - 100 %;Sliver CAS:(7440-22-4) 1 - 10 %;rosin CAS:(8050-09-7) 1 - 10 %;Copper Metal CAS:(7440-50-8) 0.1 - 1 %:2.2'.2"-Nitriotriethanol



(EN) Warning: May cause an allergic skin reaction,

Prevention: Avoid breathing dust furne/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF ON SKIN: Wash with pienty of water. If skin imitation or rash occurs. Get medical advice/attention. Take off contaminated clothing and wash it before

(MS) Amaran: Boleh menyebabkan tindak balas alahan kulit.

Pencegahan: Elakkan daripada menghirup habukwasapigasikabus wapisemburan. Pakalan kerja yang tercemar tidak harus dibiankan keluar dari tempat kerja. Pakai sarung tangan pelindungipakaian pelindungiperindungan mata/perindungan muka. Respons: JIKA TERKENA KULIT: Basuh dengan air yang banyak. Jika terjadi kerengsaan atau ruam kulit: Dapatkan nasihathawatan perubatan. Tanggalkan

pakalan yang tercemar dan basuh sebelum digunakan semula.



Changes to Solder Wire Reel (Top) Labels







Henkel Version


Harima Version



Changes to Solder Wire Reel (Base) Labels







Henkel Version

Harima Version



Changes to Solder Wire Box Labels



Henkel (M) Sdn Bhd Lot 62049 Jalan Portland, Tasek Industrial Estate, 31400 Ipoh, Perak Darul Ridzuan, Malaysia Tel:80-5-5478811 Fav:80-5-547188 www.henkel.com/electronics Made in Malaysia





ALLOY:HMP DIAMETER: 0.56MM TYPE: ERSIN 362 PART NO:

CONTENTS: 20 X 0.25KG REELS **NET WEIGHT: 5KG** DOM: 17/May/2022 CORE:5 CORE

Henke

Bahan Pemetrian Mengandungi Plumbum, Soldering Material Containing Lead.

KNOWN AS: HMP 362 5C 0.56MM 0.25KG RLS FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call

CHEMTREC: +1 703-741-5970

Refer SDS before use Rujuk SDS sebelum guna
All marks are trademarks and/or registered trademarks of Henkel and its affiliates in the US and elsewh

Lead CAS:(7439-92-1) 60 - 100 %;Tin CAS:(7440-31-5) 1 - 10 %;Silver CAS:(7440-22-4) 1 - 10 %



(EN) Danger. May damage fertility or the unborn child. May cause harm to breast-fed children. Causes damage to organs (Blood, Klishey, Central Nervous system) through protonged or repeated exposure (inhalation-dust, oral) representation. Obtain special instructions before use. Do not breathe dustymmelgas/mistivapours/spray. Avoid contact during pregnancy and while nursing. Wash hands throughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective dolling-ye protection-dishes protection.

(MS) Bahaya: Boleh merosakkan kesuburan atau janin. Boleh memudaratkan kanak-kanak yang menyusu badan Menyebabkan kerosakan organ(darah, ginjal, sistem saraf tunjang) dengan pendedahan berpanjangan atau berulang kali (penyedutan-habuk, oral).

kanjperiyodukiritaduk, urali, Penergeladuk Dapatkan arahan khas sebelum menggunakannya. Jangan hirup habuk/wasapigas/kabus/wapisemburan. Elakkan sentuhan semasa hamilimenyasu bayi. Basuh tangan bersih-bersih selepas mengendalikan bahan. Jangan makan minum atau mencokok apabila menggunakan produk ini. Pakai sanung tangan pelidungipakaan pelindungipekan makan mata/perlindungan muka. Respons: JIKA mengalami pendedahan atau khuatir: Dapatkan nasihat/rawatan perubatan

Henkel Version



Harima Version

MULTICORE

362 HMP 5C 0.56MM R



O52F990443

Lot 62049 Jalan Portland, Tasek Industrial Estate, 31400 Ipoh, Perak Darul Ridzuan, Malaysia.

ALLOY:HMP DIAMETER: 0.56MM TYPE:ERSIN 362 CORE:5 CORE

CONTENTS: 20 X 0.25KG REELS

NET WEIGHT: 5KG DOM: 17/May/2022

Bahan Pemetrian Mengandungi Plumbum. Soldering Material Containing Lead.

Refer SDS before use Rujuk SDS sebelum guna



Harimatec Malaysia Sdn Bhd

Tel:60-5-5432000 Fax:60-5-5471868

Lead CAS:(7439-92-1) 60 - 100 %;Tin CAS:(7440-31-5) 1 - 10 %;Silver CAS:(7440-22-4) 1 - 10 %



(EN) Danger, May damage fertility or the unborn child. May cause harm to breast-fed children. Causes damage to organs (Blóod, Kidney, Central Nervous system) through prolonged or repeated exposure (inhalation-dust, oral)
Prevention: Obtain special instructions before use. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact during pregnancy and while nursing. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection Response: IF exposed or concerned: Get medical advice/attention

(MS) Bahaya: Boleh merosakkan kesuburan atau ianin. Boleh memudaratkan kanak-kanak yang menyusu badan Menyebabkan kerosakan organ(darah, ginjal, sistem saraf tunjang) dengan pendedahan berpanjangan atau berulang kali/penyedutan-habuk, oral).

Pencegahan: Dapatkan arahan khas sebelum menggunakannya. Jangan hirup habuk/wasap/gas/kabus/wap/semburan. Elakkan sentuhan semasa hamilimenyusu bayi. Basuh tangan bersih-bersih selepas mengendalikan bahan. Jangan makan, minum atau merokok apabila menggunakan produk ini. Pakai sarung tangan pelindungipakaian pelindungiperlindungan

mata/perlindungan muka. Respons: JIKA mengalami pendedahan atau khuatir: Dapatkan nasihat/rawatan perubatan



Changes to Liquid Flux Labels



Henkel (M) Sdn Bhd Lot 62049 Jalan Portland, Tasek Industrial Estate, 31400 lpoh, Tel:60-5-5476811 Fax:60-5-5471868 www.henkel.com/electronics Made in Malaysia

DOM: 20/Oct/2022

USE BY:19/Oct/2024



PART NO

FLASH POINT: 12 °C

Read SDS Before Use. Rujuk SDS Sebelum Guna

SG: 0.872

FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call CHEMTREC: +1 703-741-5970

KNOWN AS: FLUX HYDRO X20 20L NET WT: 17.440KG

All marks are trademarks and/or registered trademarks of Henkel and its affiliates in the US and elsewhere.

Propan-2-ol CAS:(67-63-0) 60 - 100 %:Givcerol CAS:(56-81-5) 10 - 30 %:Citric acid CAS:(77-92-9) 1 - 10 %:ammonium chloride CAS:(12125-02-9) 1 - 10 %

(EN) Danger: Highly flammable liquid and vapour. Causes serious eve irritation. May cause drowsiness or dizziness. Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking, Keep container tightly closed, Ground and bond container and receiving equipment. Use exclosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing

dustfurme/gas/mist/vapours/spray. Wash hands thoroughly after handling. Wear protective gloves, eye protection, and face protection.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, if eye imitation persists: Get medical advice/attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction

(MS) Bahaya: Cecair dan wap amat mudah terbakar Menyebabkan kerengsaan mata yang serius Boleh menyebabkan mengantuk atau kepeningan Pencegahan: Jauhkan dari hababunga apilapi terdedah/pemukaan panas. Jangan merokok, Bekas hendaklah sentiasa ditutup ketat. Pembumian/pengikatan harus disediakan pada bekas dan peralatan penerima. Gunakan peralatan tahan letupan. Gunakan hanya alat yang tidak menyebabkan bunga api. Ambil langkah waspada terhadap nyahcas statik. Elakkan daripada menghirup habukwasapigasikabusiwapisemburan. Basuh tangan bersih-bersih selepas

mengendalikan bahan. Pakaliah sarung tangan, perlindungan mata dan muka.
Respons: JIKA PADA KULIT (atau rambut): Tanggalkan dengan serta merta semua pakaian yang tercemar. Bilas kulit dengan airimandi pancuran. JIKA dihidu: Pindahkan mangsa ke tempat udara segar dan biarkan rehat dalam kedudukan yang selesa untuk bernafas. Hubungi PUSAT RACUN atau doktor jika anda merasa kurang sihat JIKA TERMASUK MATA: Bilas dengan hati-hati menggunakan air selama beberapa minit. Tanggalkan kanta lekap, jika dipakai dan mudah dtanggalkan. Teruskan membilas. Jika kerengsaan mata tidak lega: Dapatkan nasihat/rawatan perubatan. Jika berlaku kebakaran: Gunakan pasir kering, bahan





Henke

IULTICORE HYDX-20 20L

PART NO O52K993037

322453 LOT NO DOM: 20/Oct/2022 FLASH POINT: 12 °C

SG: 0.872

USE BY:19/Oct/2024 NET WT: 17.440KG

Read SDS Before Use. Rujuk SDS Sebelum Guna

Propan-2-ol CAS:(67-83-0) 60 - 100 %;Glycerol CAS:(56-81-5) 10 - 30 %;Citric acid CAS:(77-92-9) 1 - 10 %;ammonium chloride CAS:(12125-02-9) 1 - 10 %

(EN) Danger. Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing

dustifume/gas/mistivapours/sgray. Wash hands thoroughly after handing. Wear protective gloves, eye protection, and face protection.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower). IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye intitation persists: Get medical advice/attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction





Harimatec Malaysia Sdn Bhd

Perak Darul Ridzuan, Malaysia. Tel:60-5-5432000 Fax:60-5-5471868

Lot 62049 Jalan Portland, Tasek Industrial Estaté, 31400 Ipoh,

(MS) Bahaya: Cecair dan wap amat mudah terbakar Menyebabkan kerengsaan mata yang serius Boleh menyebabkan mengantuk atau kepeningan Pencegahan: Jauhkan dari haba/bunga api/api terdedah/permukaan panas. Jangan merokok. Bekas hendaklah sentiasa ditutup ketat. Pembumian/pengikatan harus disediakan pada bekas dan peralatan penerima. Gunakan peralatan tahan letupan. Gunakan hariya alat yang tidak menyebabkan bunga api. Ambil langkah waspada terhadap nyahcas statik. Elakkan daripada menghirup habuk/wasap/gas/kabus/wap/semburan. Basuh tangan bersih-bersih selepas engendalikan bahan. Pakailah sarung tangan, perindungan mata dan muka.

Respons: JIKA PADA KULTT (atau rambut): Tangalikan dengan serta merta semua pakaian yang tercemar. Bilas kulit dengan airimandi pancuran. JIKA dihidu: Pindahkan mangsa ke tempat udara segar dan biarkan rehat dalam kedudukan yang selesa untuk bemafas. Hubungi PUSAT RACUN atau doktor jika anda merasa kurang sihat JIKA TERMASUK MATA: Bilas dengan hati-hati menggunakan air selama beberapa minit. Tanggalkan kanta lekap, jika dipakai dan mudah ditanggalikan. Teruskan membilas. Jika kerengsaan mata tidak lega: Dapatkan nasihat/rawatan perubatan. Jika berlaku kebakaran: Gunakan pasir kering, bahan kimia kering atau alkohol tahan busa untuk kepupusan.

Henkel Version



Harima Version



