

APPLICABLE STANDARD						
RATING	OPERATING TEMPERATURE RANGE	-40°C TO 105°C(<i>note1</i>)	STORAGE TEMPERATURE RANGE	-10°C TO 50°C (PACKED CONDITION)		
	VOLTAGE	50 V AC / DC	OPERATING OR STORAGE HUMIDITY RANGE	RELATIVE HUMIDITY 90 % MAX (NOT DEWED)		
	CURRENT	0.5 A (<i>note2</i>)	APPLICABLE CABLE	t=0.3±0.05mm, GOLD PLATING (GND PLATE: t=0.5±0.05mm, TIN PLATING)		
SPECIFICATIONS						
ITEM		TEST METHOD		REQUIREMENTS	QT AT	
CONSTRUCTION						
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	×	×
MARKING		CONFIRMED VISUALLY.			×	×
ELECTRICAL CHARACTERISTICS						
VOLTAGE PROOF		150 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.	×	×
INSULATION RESISTANCE		100 V DC.		500 MΩ MIN.	×	×
CONTACT RESISTANCE		AC 20 mV MAX (1 KHz) , 1 mA .		100 mΩ MAX. INCLUDING FFC BULK RESISTANCE (L=8mm)	×	×
MECHANICAL CHARACTERISTICS						
VIBRATION		FREQUENCY 10 TO 55 Hz, HALF AMPLITUDE 0.75 mm, — m/s ² FOR 10 CYCLES IN 3 AXIAL DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② CONTACT RESISTANCE: 100 mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—
SHOCK		981 m/s ² , DURATION OF PULSE 6 ms AT 3 TIMES IN 3 BOTH AXIAL DIRECTIONS.				
MECHANICAL OPERATION		20 TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 100 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—
FFC RETENTION FORCE		MEASURED BY APPLICABLE FPC. (THICKNESS OF FFC SHALL BE t=0.30mm AT INITIAL CONDITION.)		DIRECTION OF INSERTION: 0.3N × n MIN.	×	—
ENVIRONMENTAL CHARACTERISTICS						
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -40→+15 TO +35→+105→+15 TO +35°C TIME 30→ 2 TO 3 → 30 → 2 TO 3 min UNDER 5 CYCLES.		① CONTACT RESISTANCE: 100 mΩ MAX. ② INSULATION RESISTANCE: 50 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2°C, RELATIVE HUMIDITY 90 TO 95 %, 96 h.			×	—
DAMP HEAT, CYCLIC		EXPOSED AT -10 TO +65 °C, RELATIVE HUMIDITY 90 TO 96 %, 10 CYCLES, TOTAL 240 h.		① CONTACT RESISTANCE: 100 mΩ MAX. ② INSULATION RESISTANCE: 1 MΩ MIN. (AT HIGH HUMIDITY) ③ INSULATION RESISTANCE: 50 MΩ MIN. (AT DRY) ④ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—
DRY HEAT		EXPOSED AT 105±2 °C, 96 h.		① CONTACT RESISTANCE: 100 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—
COLD		EXPOSED AT -40±3°C, 96 h.			×	—
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
	7	DIS-F-00001058	HK. KINOUCHI	HS. SAKAMOTO	16. 02. 02	
REMARK				APPROVED	MO. ISHIDA	09. 07. 07
				CHECKED	YN. TAKASHITA	09. 07. 07
				DESIGNED	YK. OTSUKA	09. 07. 07
				DRAWN	YK. OTSUKA	09. 07. 07
Unless otherwise specified, refer to IEC 60512.						
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-325208-00	
	SPECIFICATION SHEET		PART NO.	FH41-**S-0. 5SH (05)		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL580		1/2

SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CORROSION SALT MIST	EXPOSED AT 35±2℃ , 5 % SALT WATER SPRAY FOR 96 h.	① CONTACT RESISTANCE: 100 mΩ MAX. ② NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—	
SULPHUR DIOXIDE ⚠ [JIS C 60068-2-42]	EXPOSED AT 40±2℃ , RELATIVE HUMIDITY 80±5% ,25±5 ppm FOR 96 h.		×	—	
HYDROGEN SULPHIDE ⚠ [JIS C 60068-2-43]	EXPOSED AT 40±2℃ , RELATIVE HUMIDITY 80±5% ,10 TO 15 ppm FOR 96 h.		×	—	
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, 245±5℃ FOR IMMERSION DURATION, 2±0.5 sec.	A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.	×	—	
RESISTANCE TO SOLDERING HEAT	1) REFLOW SOLDERING PEAK TMP. 250℃ MAX . REFLOW TMP. OVER 230℃ WITHIN 60 sec. 2) SOLDERING IRONS : TMP. 350±10℃ FOR 5±1 sec .	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	×	—	